

## 1. Features

- Green and Power Saving Available
- Equivalent Full Range Temperature Coefficient 30ppm/ °C
- Temperature-Compensated for Operation over Full Rated Operating
- Adjustable Hold on Current and Hold on Switch Timing
- No Output Noise
- Fast Turn-on Response
- RoHS Compliant, 100% Pb & Halogen Free



## 2. Description

PBB series control box is a small interface electronic device integrated into the DIN43650 Type B connector, improving the service life and performance of the solenoid valve. This product is designed with a power-saving circuit to reduce the coil temperature so that the valve can operate normally when opening and closing. PBB series power conversion circuits do not present any EMI issues. Additionally, an added a blinking LED indicator to notify that it has entered power-saving mode.(note1) The extent of power-saving or the time required to enter power-saving mode can be adjusted according to the customer's needs. For different coils and solenoid valves, PBB series can provide different power-saving effects and adjust parameters to accommodate customers' applications.

**Note1** : LED is darker while power saving mode active , LED is always bright in case of power saving mode suspend

## 3. Applications

- Solenoid Valve
- Valve Terminal
- Electric locks
- Switchgear



### 4. Technical Data

- 12/24VDC(-10%/+10%) Operating Vcc Range
- Pulse Output Current : 500mA max.
- Continue Output Current : 300mA max. (Adj.)
- Power Saving Ratio : high to 80% (note1)
- Power Saving Covert Time 0~999mS Adj.(+/-10%)
- No EMI & Magnet Loss , Thermal Reduce
- No magnetic noise during operation
- Operating temperature -20C ~ 85C
- Module Model : PB Series

**Note2** : depends on coil specification & solenoid on/off timing

**Note3** : build in fuse on board to be safety issue upon surge power occur

### 5. Electrical Parameter Table

parameter		minimum	maximum	unit
Power Supply On	12V	10.8	13.2	V
	24V	21.6	26.4	
Maximum pulse current			0.5	A
Maximum cont. current			0.15(24V) , 0.3(12V)	A
Allowed coil resistance		full range		Ohm
pull in time		1	999	mS
holder power	0.1W	90	110	mW
	0.2W	180	220	
	0.3W	270	330	
	0.5W	450	550	
ESD protection		4000		V
Operating Temperature(note2)		-20	85	°C

**Note2** . standard continuous holding power maxim time length is 4hrs.

**Note3** . If your application is out of the specifications listed above. We can then customize the driver to meet your most demanding needs.

**Note4**. The driver closes automatically at voltages below the minimum operating voltage and eliminates the coil discharge voltage.





9. Ordering Information

**PBB-VV-WW-SS**

VV: Input Voltage range [unit:V]

VV value	12	24
Vcc min [ V ]	10.8	21.6
Vcc max [ V ]	13.2	26.4

WW: Holding power[unit:mW]

WW value	01	03	05
P hold [ mW ]	100	300	500

SS: Translate Time (second stage time)[unit:ms]

SS value	20	35	50
Delay time	200ms	350ms	500ms

Copy Rights and Disclaimer

This document may not be reproduced or duplicated, in any form, in whole or in part without prior written consent of MIT . Copyrights © 2023, MIT-Magnetic Integrated Technology Incorporated. MIT-Magnetic Integrated Technology reserves the right to make changes to the information published in this document at anytime without notice. MIT' s products are limited for use in industrial and normal commercial applications. MIT' s products are not to be used in any device or system, including but not limited to medical life support equipment and system.